

|           |    |         |         |         |         |      |
|-----------|----|---------|---------|---------|---------|------|
| 框架        |    | 63M     | 71M     | 80M     | 90M     |      |
| 輸出        |    | 1/4HP   | 1/2HP   | 1HP     | 2HP     | 3HP  |
| 效率        |    | >77%    | >81%    | >85%    | >90%    | >91% |
| 額定轉速      |    | 3600rpm | 3600rpm | 3600rpm | 3600rpm |      |
| 腳座安裝尺寸    | A  | 100     | 112     | 125     | 140     |      |
|           | B  | 80      | 90      | 100     | 125     |      |
|           | V  | 40      | 45      | 50      | 56      |      |
|           | H  | 63      | 71      | 80      | 90      |      |
|           | K  | 7       | 7       | 9       | 10      |      |
|           | BA | 126     | 130     | 155     | 171     |      |
| 軸         | D  | 11      | 14      | 19      | 24      |      |
|           | E  | 23      | 30      | 40      | 50      |      |
| B5凸緣安裝尺寸  | XX | 122     | 122     | 156     | 158     |      |
|           | M  | 130     | 130     | 165     | 165     |      |
|           | N  | 110     | 110     | 130     | 130     |      |
|           | P  | 160     | 160     | 200     | 200     |      |
|           | S  | 10      | 10      | 12      | 12      |      |
|           | T  | 3.5     | 3.5     | 3.5     | 3.5     |      |
| B14凸緣安裝尺寸 | M  | 75      | 85      | 100     | 115     |      |
|           | N  | 60      | 70      | 80      | 95      |      |
|           | P  | 90      | 105     | 120     | 140     |      |
|           | S  | M5      | M6      | M6      | M8      |      |
|           | T  | 2.5     | 2.5     | 3       | 3       |      |
| 一般尺寸 (參考) | L  | 229     | 234     | 270     | 350     |      |
|           | AD | 102     | 103     | 125     | 135     |      |
|           | HA | 165     | 174     | 205     | 225     |      |
|           | X  | N/A     | N/A     | N/A     | N/A     |      |